

## Models / S70 Skid-Steer Loader

# Overview & Specifications



The Bobcat® S70 skid-steer loader is small enough to get in the tight spots, yet tough enough to get you out. This agile little workhorse is only 6 ft. tall and 3 ft. wide — the ideal size for quickly moving through narrow doorways, corridors, aisles, alleys and gates, and for working under low ceilings. It's the perfect skid steer loader whenever the job is too big for a shovel or the space is too small for a larger machine.

<b>Horsepower</b>	<b>Rated Operating Capacity</b>
17.5 kW	318 kg
<b>Operating Weight</b>	<b>Auxiliary Std Flow</b>
1268 kg	37.1 l/min
<b>Auxiliary High Flow</b>	<b>Joystick Control</b>
N/A	N/A

[ASK FOR QUOTE >](#)

[DOWNLOAD BROCHURE >](#)

*\*Specifications and design are subject to change without notice.  
\*Pictures of product may show other than standard equipment.*

## Specifications & Options

Standard    Optional   **N/A** Not Applicable

## Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	17.5 kW
Turbocharged Engine	N/A

## Performance

Rated Operating Capacity (ISO)	318 kg
Tipping Load	686 kg
Operating Weight	1268 kg
Travel Speed	9.8 km/h

## Capacities

Fuel Tank	24.6 l
-----------	--------

## Hydraulic System

System Relief @ Quick Couplers	206.84 bar
Auxiliary Std Flow	37.1 l/min
Auxiliary High Flow	n/a

## Dimension

<b>Length</b>	1920 mm
<b>Length without Attachment</b>	1920 mm
<b>Length with Standard Bucket</b>	2471 mm
<b>Width</b>	902 mm
<b>Width (with bucket)</b>	914 mm
<b>Height</b>	1814 mm
<b>Height with Operator Cab</b>	1814 mm
<b>Height to Bucket Hinge Pin</b>	2400 mm
<b>Reach @ Maximum Height</b>	401 mm
<b>Turning Radius</b>	1491 mm
<b>Wheelbase</b>	721 mm

# Features

Joystick Control	N/A
Air Conditioning	N/A
Adjustable Seat	■
Backup Alarm	■
BICS System (Interlock)	■
Cab Enclosure	✓
Sound Option	✓
Cab Heater	✓
Operating Lights	■
Parking Brake	■
Radio	N/A
Rear Window	■
Top Window	✓
Lift-Arm Support	■
Seat Belt	■
Suspension Seat	✓
Two Speed Travel	N/A
Deluxe Instrumentation	N/A
Engine Shutdown	N/A
Hydraulic Bucket Positioning	✓
High Flow Option	N/A
Auxiliary Hydraulics	■
Spark Arrestor Muffler	■
Bob-Tach Attachment System	■
Power Bob-Tach	N/A
ACS (Switchable Controls)	N/A
Ride Control	N/A
Rear Hydraulics	N/A



Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.